

AC230V LED Strip Light

Driverless, Overvoltage Protection

SL728W120A





Key Feature

- ◆ LM-80 approved LED
- ◆ High efficiency
- ◆ 50,000 hours Lifetime, 3 years warranty
- ◆ Multiple Color Option : 1800K ~ 6500K
- ◆ Only one Bin, SDCM<3, or SDCM<2 available
- ◆ CRI Option: Ra>95+, Rf>95 and Rg=100 all available

1. Specification & Parameters:

1.1 External Dimension




Notice:

Maximum Input Voltage: AC 230V

Size of each section is 10cm, and cutting at "black line" place.

The dimension tolerance of height is $\pm 0.3\text{mm}$, and tolerance of width is $\pm 0.3\text{mm}$.



1.2 Technical Parameters

Technical Data


Product Code	SL728W120A	
Colour	W/WW/R/G/B	
Working Voltage	AC230V, 50Hz	
LED Qty/m	120LEDs /m	
LED Type	SMD 2835	
CRI	CRI > 80	CRI > 90
Rated Power/m	12W/m	12W/m
Light Efficiency $\pm 10\%$	110Lm/w	90Lm/w
LED Distance	8.33mm	
Min. Cutting LED	12LEDs	
Min. Cutting Length	10cm	
Weight/m	120g	
Storage Temperature	-25~60°C (-13~140°F)	
Environmental Working Temperature	-20~45°C (-4~113°F)	
IP Rating	IP65 (uncut) void if cut	




1.3 Optical Parameters

Optical Data			Lumen/m		
Product Code	MF728W120A				
		Rated CRI	CRI80	CRI90	
Color	Wavelength	CCT			
Ultra WW	/	2000K±100K	1028 lm/m	840 lm/m	
Super WW	/	2400K±100K	1080 lm/m	900 lm/m	
Warm White	/	2725K±100K	1200 lm/m	960 lm/m	
Warm White	/	3045K±150K	1260 lm/m	1020 lm/m	
Natural White	/	4000K±150K	1320 lm/m	1080 lm/m	
Day White	/	5000K±200K	1320 lm/m	1080 lm/m	
Cool White	/	6500K±250K	1320 lm/m	1080 lm/m	
RED	620-630nm	/	/	/	
GREEN	520-530nm	/	/	/	
BLUE	465-475nm	/	/	/	
AMBER	585-595nm	/	/	/	

Luminous Intensity Distribution





illumination diagram



2. Types of Connector

2.1 Outdoor Use & IP65 Waterproof Connector



> Notes:

- IP65 Outdoor Use: Pls do not cut off the LED Tape light, and DIY cutting is not allow;
- All kinds of customized length of the light are available, from 10cm minimum ~ 50m maximum ;
- Do not submerge LED Tape light in any liquids, or use the light in the vicinity of standing water;
- Outdoor Application Scope: Outer Wall of building, Overbridge etc., and Suitable for raining environments;

2.2 Indoor use & DIY IP40 Connector




Power Cord

Connects light to power supply
IP40 DIY connector (indoor use)

Cable Length available in 0.3m min ~ 20m Max.

Screwless Terminal DIY assembly

- AC Plug (2 Pin) *1
- Anti-tension Shell *1
- PC Fixing Clip *1




Docking Connector

Combine two pieces of the lights together
IP40 DIY connector (indoor use)

Seamless Docking, Screwless Terminal

- Anti-tension Shell *1
- Feed Connector (2 Pin) *1
- PC Fixing Clip *2




L-Type Connector

Combine two pieces of the lights together
IP40 DIY connector (indoor use)

Seamless Docking, Screwless Terminal

- L-Type Anti-tension Shell *1
- L-Type Feed Connector (2 Pin) *1
- PC Fixing Clip *2




End Cap

Termination Protection of the light,
IP40 DIY connector (indoor use)

Screwless Terminal DIY assembly

- Anti-tension Shell *1
- PC Fixing Clip *1






> Notes:

- Before making any cuts, installation, maintenance or connection, and be sure the light is power-off!
- IP40 Indoor Use: Pls cut the light and assemble all connectors according to the instruction manual;
- Don't install and light up and use the light under water, Only IP40 application places can be used for this light;
- Indoor Application Scope: Cove of Theater, and cove of hotel lobby etc., and Suitable for dry and anti-dust environments;

3. Installation & Profile

3.1 Plastic Profile







Code	W*H(ft)	Profile Length(mm)	Hole Size (mm)	Hole Number (pcs)
MF728W120-01	17mm * 8.8mm	500mm	Φ3.5mm	2
		1000mm	Φ3.5mm	3
		1500mm	Φ3.5mm	5
		2000mm	Φ3.5mm	7

Notes:

1. Plastic Profiles's raw material is PC, white/black/red paint available;
2. Any customized Length available too, such as 0.5m or 1m or 1.5m, and 2m length maximum;
3. Each 0.3m length with 1 hole and 1 screw, and installation referece to the user manual;

3.2 Plastic Mounting Clip



Notes:


1. Mounting Clip's raw material is PC, and transparent/white/black/red paint available;
2. Each 0.3m length with 1 Mounting Clip +1 screw, and installation referece to the user manual;

4. Installation & Profile


4.1 Reel packaging for projects



50m/roll



1 roll in one Carton



Master Carton

4.2 Reel packaging for retails



Light Length (m/one roll)	Carton Dimension (cm)	Light Number (rolls)	Carton Weight (kg)
20m	25*21*33	1 roll	3.5
30m	31*23*39	1 roll	4.8
40m	31*23*39	1 roll	6.2
50m	34*27*43	1 roll	7.9

5. Certificate & Reliability

Certificate

Item	STANDARD AND DESCRIPTION	Report Reference
CE & ROHS		
CE Certificate	TÜV Rheinland	Testing in the TUV Lab
ROHS	TÜV Rheinland	Testing in the TUV Lab